



The Cryogenic Storage Ring CSR: Stored and cooled ions in a 10 K environment

Claude Krantz

Max Planck Institute for Nuclear Physics





The Cryogenic Storage Ring **CSR**

Status of the CSR

Electron **Cooler**

(Some) experimental **perspectives**






The CSR






The CSR





The CSR




circumference:	35 m
beam energy:	20 keV \times q ... 300 keV \times q
temperature:	10 ... 300 K
res. gas press. (@ < 10 K):	10^{-13} mbar (~ 1000 cm⁻³)



injection energy: 20 ... 300 keV

The CSR



**Electrostatic ion optics
(mass independent)**

**Fully cryogenic
(10 K) beam line**

circumference:	35 m
beam energy:	$20 \text{ keV} \times q \dots 300 \text{ keV} \times q$
temperature:	10 ... 300 K
res. gas press. (@ < 10 K):	10^{-13} mbar ($\sim 1000 \text{ cm}^{-3}$)


m/q range:	1 ... “∞” u/e
lowest rigidity	p^+, H^- @ 20 keV





injection energy: 20 ... 300 keV

The CSR



circumference:	35 m
beam energy:	$20 \text{ keV} \times q \dots 300 \text{ keV} \times q$
temperature:	10 ... 300 K
res. gas press. (@ < 10 K):	10^{-13} mbar ($\sim 1000 \text{ cm}^{-3}$)

m/q range:	1 ... “∞” u/e
lowest rigidity	p^+, H^- @ 20 keV



... with electron cooling	
m/q range:	1 ... 160 u/e (@ 300 kV)
lowest rigidity	p^+, H^- @ 20 keV



The CSR

Electrostatic beam optics

- 4-fold symmetric storage ring
All CSR corner sections identical
- 4 x 2 pairs of **focussing quadrupoles**
- 4 x 2 **6°-deflector** electrodes (20 kV)
- 4 x 2 **39°-deflector** electrodes (20 kV)
- 4 free straight sections (2.4 m each)







The CSR

Electrostatic beam optics

- 4-fold symmetric storage ring
All CSR corner sections identical
- 4 x 2 pairs of **focussing quadrupoles**
- 4 x 2 **6°-deflector** electrodes (20 kV)
- 4 x 2 **39°-deflector** electrodes (20 kV)
- 4 free straight sections (2.4 m each)








The CSR

Cryogenics

- Multi-layer cryostat
- Inner vacuum chamber (≤ 10 K) cooled by superfluid He (20 W).
- 2 radiation shields (40 and 80 K) cooled by 5-K He (600 W)
- Superinsulation
- Isolation vacuum chamber








The CSR

Cryogenics

- Multi-layer cryostat
- Inner vacuum chamber (≤ 10 K) cooled by superfluid He (20 W).
- 2 radiation shields (40 and 80 K) cooled by 5-K He (600 W)
- Superinsulation
- Isolation vacuum chamber





The CSR

XHV: Extremely High Vacuum




- In 300-K-operation: $\sim 10^{-11}$ mbar

250°C bakeout,

Ion-getter pumps,

NEG surfaces,


bakeable charcoal cryopumps



- In < 10-K-operation: $\approx 10^{-13}$ mbar RTE


cryoabsorption at 10-K-walls,

2-K cryocondensation pumps






Present Status





Present Status



Assembly of **inner chambers and ion optics.**





Present Status

Assembly of **inner chambers and ion optics.**






Present Status

Assembly of inner chambers and ion optics.



High-temperature bake out (**250°C**) and cryogenic (**10 K**) test of **1st corner**.






Present Status

Assembly of inner chambers and ion optics.



High-temperature bake out (**250°C**)
and cryogenic (**10 K**) test of **1st corner**. ✓
High-voltage (25 kV) test of optics.





Present Status

Assembly of inner chambers and ion optics.

High-temperature bake out (250°C)


and cryogenic (10 K) test of 1st corner. ✓

High-voltage (25 kV) test of optics. ✓

300 kV injector



CSR main injector:
 $\pm 300 \text{ kV}$





Present Status


Assembly of inner chambers and ion optics.

High-temperature bake out (250°C)

and cryogenic (10 K) test of 1st corner.

High-voltage (25 kV) test of optics.

300 kV injector






Present Status

Assembly of inner chambers and ion optics.

High-temperature bake out (250°C) and cryogenic (10 K) test of 1st corner.

High-voltage (25 kV) test of optics.

300 kV injector





Present Status


Assembly of inner chambers and ion optics.

High-temperature bake out (250°C)

and cryogenic (10 K) test of 1st corner.

High-voltage (25 kV) test of optics.

300 kV injector





Present Status

Assembly of inner chambers and ion optics.



High-temperature bake out (250°C) and cryogenic (10 K) test of 1st corner.




High-voltage (25 kV) test of optics.




300 kV injector.



Beam diagnostics




position-,
Schottky-,
current-
pickups



beam
imaging
system

ion
beam





Present Status

Assembly of inner chambers and ion optics.



High-temperature bake out (250°C) and cryogenic (10 K) test of 1st corner.



High-voltage (25 kV) test of optics.



300 kV injector.





Beam diagnostics



Commissioning (room temperature):

Ar+ (50 keV)

Inject $^{40}\text{Ar}^+$ at 50 keV





Present Status

Assembly of inner chambers and ion optics.

High-temperature bake out (**250°C**)

and cryogenic (10 K) test of 1st corner.

High-voltage (25 kV) test of optics.

300 kV injector

1

500 kV injector: Beam diagnostics

4



Beam diagnostics Commissioning (room temperature):

1

Inject $^{40}\text{Ar}^+$ at 50 keV

17th March 2014 (15:33)

First stored beam!





Present Status

Assembly of inner chambers and ion optics.



High-temperature bake out (250°C) and cryogenic (10 K) test of 1st corner.



High-voltage (25 kV) test of optics.



300 kV injector.



Beam diagnostics

Commissioning (room temperature):

Inject ${}^{40}\text{Ar}^+$ at 50 keV



17th March 2014 (15:33)

First stored beam!



Beam lifetime




(~3 ms @ ~ 10^{-7} mbar)

Detector tests

Betatron stability

rf bunching

...





Present Status

Assembly of **inner chambers and ion optics.**



High-temperature bake out (**250°C**)



and cryogenic (**10 K**) test of **1st corner.**



High-voltage (25 kV) test of optics.



300 kV injector.



Beam diagnostics



Commissioning (room temperature):



Inject $^{40}\text{Ar}^+$ at 50 keV



17th March 2014 (15:33)



First stored beam!



Beam lifetime



(~3 ms @ $\sim 10^{-7}$ mbar)



Detector tests



Betatron stability



rf bunching



...




Next step:

Cryogenic operation



Electron Cooler





Electron Cooler

Principle of ecooling:



$$v_{\text{electron}} = v_{\text{ion}}$$

CSR energy limit: $E_{\text{ion}}/Z_{\text{ion}} = 300 \text{ keV}$ → Need **very** slow electrons

160 eV for p^+

< 20 eV for most ions


1 eV for $M_{\text{ion}} = 160 \text{ u}$



600
km/s




Electron Cooler






Electron Cooler





Electron Cooler





Electron Cooler

Electron energy: towards 1 eV and below ...

- Calibration of E_e against cathode potential taking beam **space charge** and **work function** differences into account

- Current:**
few μA at $E_{\text{cool}} = 1 \text{ eV}$



$$n_e \sim 10^5 \text{ cm}^{-3}$$

- Cooling times

$$\tau \sim \frac{M_{\text{ion}} T_e^{3/2}}{Z_{\text{ion}}^2 n_e}$$

up to $\sim 100 \text{ s} \dots$

... but: ion lifetime $\sim 1000 \text{ s}$





Electron Cooler

Electron energy: towards 1 eV and below ...

- Calibration of E_e against cathode potential taking beam **space charge** and **work function** differences into account

- Current:**
few μA at $E_{\text{cool}} = 1 \text{ eV}$




$$n_e \sim 10^5 \text{ cm}^{-3}$$

- Cooling times

$$\tau \sim \frac{M_{\text{ion}} T_e^{3/2}}{Z_{\text{ion}}^2 n_e}$$

up to $\sim 100 \text{ s} \dots$

... but: ion lifetime $\sim 1000 \text{ s}$




TSR data, C. K. et al., in prep.






Electron Cooler - Status



Superconducting ring coils have
been built and tested

(LNe, approx. 30 K)


10-K vacuum chambers are in
manufacturing process ...






Electron Cooler - Status

assembly of 300 K
beamlines ...






Electron Cooler - Detectors







Electron Cooler - Detectors



from
experiment


COMPACT

“Cold Movable
Particle Counter”





Electron Cooler - Detectors





from
experiment →




COMPACT

**“Cold Movable
Particle Counter”**






Electron Cooler - Detectors




NICE

“Neutral Imaging in
Cryogenic Environment”




from
experiment →






Electron Cooler -






NICE

“Neutral Imaging in
Cryogenic Environme




N_2^+ from
experiment
(50 keV)






Electron Cooler -






NICE

“Neutral Imaging in
Cryogenic Environment”



N_2^+ from
experiment
(50 keV)





(A few) Experimental Perspectives

Electrostatic optics (300 keV/q)

Well-suited for low charge/mass-ratio
(e.g. complex molecules, clusters,
low-charge atomic ions)



Extremely High Vacuum (10^{-13} mbar)

Storage of large or heavy (= slow)
ions for long times ($\sim 1000 \text{ s}$)



Internally and kinematically cold ions

10 K environment: Internal cooling of molecules
Electron cooler: phase space cooling






(A few) Experimental Perspectives

Phase 1 (2014):

Commissioning of CSR (300 K) ✓

Storage at 10 K

→ Experiments with uncooled beam
(but: radiative cooling!)



Phase 2 (2015 → ...):

Installation of **electron cooler**


→ Experiments with cooled beams (internal AND external!)

→ Experiments on electron-ion interaction (DR et al ...)






Phase 1 Experiments







Phase 2 Experiments: Recombination





DR Experiments: “Benchmarks”





DR Experiments: “Benchmarks”



at CSR: $E_{cool} = 54$ eV
 $10\text{ K} \rightarrow J=0$



DR Experiments: Complex Systems

- Polyatomics: H_3^+ , H_3O^+ , $\text{HNO}^+/\text{HON}^+$, $\text{CCN}^+/\text{CNC}^+$...
- Recombination of large organic molecules C_xH_y^+ , $\text{C}_x\text{H}_y\text{OH}^+$...
- Dielectronic Recombination of atomic monoions: C^+ , N^+ , F^+ , Si^+ , P^+ , Cl^+ , Fe^+
Contribute to cold astrochemistry [Bryans et al., ApJ 694 (2009)]
$$\text{C}^+ ({}^2\text{P}_{1/2}) + \text{e}^- (< 8 \text{ meV}) \rightarrow \text{C}^{**} ({}^2\text{P}_{3/2}, nl) \rightarrow \text{C}^* + \gamma$$

(Not measurable in TSR due to field ionisation and non-DR background!)
- Electron cooled cluster anions ...
- Ion-photon interactions / ion-neutral collisions with cooled/cold ions.





Summary

CSR, a **next-generation electrostatic storage ring** has been been commissioned in 2013.

It will be **all-cryogenic**, providing very low residual gas density and IR background radiation.

It will feature a fully-functional **electron cooler**.

It provides unique opportunities for a multitude of experiments **stored and cooled** low energy ions.





Thank You!



**Max Planck Institute for Nuclear Physics,
Heidelberg**

Klaus Blaum

Robert von Hahn

Florian Fellenberger

Sebastian George

Sebastian Menk

Holger Kreckel

Florian Grussie

Philipp Herwig

Arno Becker

C. K.

Aodh O'Connor

Stephen Vogel

Robert Repnow

Manfred Grieser

Andreas Wolf

Université Catholique,

Louvain-la-Neuve



Xavier Urbain

**Justus-Liebig University,
Gießen**



Kaija Spruck

Stefan Schippers

**Columbia University,
New York**



Oldřich Novotný

Daniel W. Savin








The CSR

Electrostatic beam optics

- Electrodes **thermally anchored** to cold chamber walls ($\leq 10\text{ K}$) ...
- ... but **mechanically decoupled** from them.
(thermal shrinking of beam pipe)







The CSR


Electrostatic beam optics

- Electrodes **thermally anchored** to cold chamber walls (≤ 10 K) ...
- ... but **mechanically decoupled** from them.
(thermal shrinking of beam pipe)





Electron Cooler - Detectors




from
experiment



future upgrade:

PIZZA
segmented microcalorimeter

36 mm



CH_3^+ @ 150 keV



A. Fleischmann, C. Enss et al.
KIP, University of Heidelberg